

Table 7: Pedestrian Crossover Selection Matrix

Two-way Vehicular Volume			Posted Speed Limit (km/h)	Total Number of Lanes for the Roadway Cross Section ¹			
Time Period	Lower Bound	Upper Bound		1 or 2 Lanes	3 lanes	4 lanes w/raised refuge	4 lanes w/o raised refuge
8 Hour	750	2,250	≤50	Level 2 Type D	Level 2 Type C ³	Level 2 Type D ²	Level 2 Type B
4 Hour	395	1,185		Level 2 Type C	Level 2 Type B	Level 2 Type C ²	Level 2 Type B
8 Hour	750	2,250	60	Level 2 Type D	Level 2 Type B	Level 2 Type D ²	Level 2 Type B
4 Hour	395	1,185		Level 2 Type C	Level 2 Type B	Level 2 Type C ²	Level 2 Type B
8 Hour	2,250	4,500	≤50	Level 2 Type D	Level 2 Type B	Level 2 Type D ²	Level 2 Type B
4 Hour	1,185	2,370		Level 2 Type C	Level 2 Type B	Level 2 Type C ²	Level 2 Type B
8 Hour	2,250	4,500	60	Level 2 Type D	Level 2 Type B	Level 2 Type D ²	Level 2 Type B
4 Hour	1,185	2,370		Level 2 Type C	Level 2 Type B	Level 2 Type C ²	Level 2 Type B
8 Hour	4,500	6,000	≤50	Level 2 Type C	Level 2 Type B	Level 2 Type C ²	Level 2 Type B
4 Hour	2,370	3,155		Level 2 Type B	Level 2 Type B	Level 2 Type C ²	Level 2 Type B
8 Hour	4,500	6,000	60	Level 2 Type C	Level 2 Type B	Level 2 Type C ²	Level 2 Type B
4 Hour	2,370	3,155		Level 2 Type B	Level 2 Type B	Level 2 Type C ²	Level 2 Type B
8 Hour	6,000	7,500	≤50	Level 2 Type B	Level 2 Type B	Level 2 Type C ²	Level 1 Type A
4 Hour	3,155	3,950		Level 2 Type B	Level 2 Type B	Level 2 Type C ²	Level 1 Type A
8 Hour	6,000	7,500	60	Level 2 Type B	Level 2 Type B		
4 Hour	3,155	3,950		Level 2 Type B	Level 2 Type B		
8 Hour	7,500	17,500	≤50	Level 2 Type B	Level 2 Type B		
4 Hour	3,950	9,215		Level 2 Type B	Level 2 Type B		
8 Hour	7,500	17,500	60	Level 2 Type B			
4 Hour	3,950	9,215		Level 2 Type B			

Type A
 Type B
 Type C
 Type D

Approaches to roundabouts should be considered a separate roadways.

¹The total number of lanes is representative of crossing distance. The width of these lanes is assumed to be between 3.0 m and 3.75 m according to MTO Geometric Design Standards for Ontario Highways (Chapter D.2). A cross sectional feature (e.g. bike lane or on-street parking) may extend the average crossing distance beyond this range of lane widths.

²Use of two sets of side mounted signs for each direction (one on the right side and one on the median)

³Use Level 2 Type B PXO up to 3 lanes total, cross section one-way.

The hatched cells in this table show that a PXO is not recommended for sites with these traffic and geometric conditions. Generally a traffic signal is warranted for such conditions.